



**TECHNICAL SPECIFICATION**

- 1 Lug type butterfly valve
- 2 Design standard API 609/EN 593
- 3 Face to face: EN 558-1 (ISO 5752)
- 4 Flange connection DIN PN10, PN16
- 5 Top flange ISO 5211
- 6 Max. working pressure 20 bar
- 7 Temperature range:  
 NBR -15°C / +80°C

W&O FIGURE	MATERIAL BODY/DISC/SEAT	TEMPERATURE
6402DX	GGG40/SUPER DUPLEX 2507/NBR	-15°C/+80°C

**DIMENSIONS**

DN (mm)	h (mm)	h1 (mm)	H1 (mm)	H2 (mm)	ØD (mm)	ØD1 (mm)	N-M (mm)	ØD2 (mm)	ØD3 (mm)	N1-Ød1 (mm)	□F (mm)	L (mm)	L1 (mm)
40	25	12	113	200	147	110	4-M16	90	70	4-10	11	33	37
50	25	12	118	208	162	125	4-M16	90	70	4-10	11	43	47
65	25	13	126	224	182	145	8-M16	90	70	4-10	11	46	50
80	25	14	133	253	197	160	8-M16	90	70	4-10	11	46	50
100	25	14	147	270	217	180	8-M16	90	70	4-10	11	52	56
125	28	14	160	298	247	210	8-M16	90	70	4-10	14	56	60
150	28	14	180	341	282	240	8-M20	90	70	4-10	14	56	60